

Lux Pro Series CXM-6

COB Arrays White LED



Features

- Below Black Body Line options: Sensus® - Hospitality White and Sensus® - Brilliant White available to provide a crisp white light and eliminate green tints
- Comprehensive CCT options including 2700K, 3000K, 3500K, 4000K, 5000K, and 6500K
- Standardized color binning available in 2 SDCM and 3 SDCM options
- Uniform optical emission with consistent color performance across all viewing angles
- Reliable long term color stability for extended product lifecycles
- High thermal conductivity designed for effective and uniform heat dissipation
- Photometric performance characterized at steady state thermal conditions to reflect actual application environments
- Utilizes KSF red phosphor technology to maximize luminous efficacy compared to conventional red phosphors



Applications

- Spotlights/Track Lights
- Downlights
- Shop Lighting
- Hospitality Lighting
- Architectural and Specialty
- Street Lighting
- Parking Lot and Area Lighting
- Tunnel Lighting

Table of Contents

Ordering Information.	2
Binning Structure.	5
Absolute Maximum Ratings.	8
Characteristics.	9
Angular Distribution and Typical Spectrum.	11
Derating Curve.	12
Mechanical Dimensions.	13
Shipping Tray Outline.	14
Shipping Label.	15
Technology Overview.	16
Test Specifications.	16
Handling Notes.	17
Revision History.	19



Ordering Information

Ordering Part Numbers - TC70 On BBL

The following tables describe products with typical flux and minimum flux measured at 150 mA and specified at $T_j = 85^\circ\text{C}$. The values at 25°C are calculated and shown for reference only.

Minimum CRI ²	CCT	Luminous Flux ¹			Ordering Part Number	
		Typical Flux (85°C)	Minimum Flux (85°C)	Calculated Typical Flux (25°C)	3-step MacAdam Ellipse	2-step MacAdam Ellipse
90	2700K	795	740	875	CXM-6-27-90-36-TC70-F8-3	CXM-6-27-90-36-TC70-F8-2
90	3000K	810	755	890	CXM-6-30-90-36-TC70-F8-3	CXM-6-30-90-36-TC70-F8-2
90	3500K	825	765	910	CXM-6-35-90-36-TC70-F8-3	CXM-6-35-90-36-TC70-F8-2
90	4000K	830	770	915	CXM-6-40-90-36-TC70-F8-3	CXM-6-40-90-36-TC70-F8-2
90	5000K	825	765	910	CXM-6-50-90-36-TC70-F8-3	CXM-6-50-90-36-TC70-F8-2
90	6500K	815	755	895	CXM-6-65-90-36-TC70-F8-3	CXM-6-65-90-36-TC70-F8-2

Notes:

1. Luminus maintains a +/- 6% tolerance on flux measurements.
2. Luminus maintains a +/- 2% tolerance on CRI measurements.



Ordering Information

Ordering Part Numbers - TC71 (Sensus® - Hospitality White) & TC73 (Sensus® - Brilliant White)

The following tables describe products with typical flux and minimum flux measured at 150 mA and specified at $T_j = 85^\circ\text{C}$. The values at 25°C are calculated and shown for reference only.

Minimum CRI ²	CCT	Luminous Flux ¹			Ordering Part Number	
		Typical Flux (85°C)	Minimum Flux (85°C)	Calculated Typical Flux (25°C)	3-step MacAdam Ellipse	2-step MacAdam Ellipse
90	2700K	790	735	870	CXM-6-27-90-36-TC71-F8-3	CXM-6-27-90-36-TC71-F8-2
	3000K	800	745	880	CXM-6-30-90-36-TC71-F8-3	CXM-6-30-90-36-TC71-F8-2
		795	740	875	CXM-6-30-90-36-TC73-F8-3	CXM-6-30-90-36-TC73-F8-2
	3500K	815	755	895	CXM-6-35-90-36-TC71-F8-3	CXM-6-35-90-36-TC71-F8-2
		805	750	885	CXM-6-35-90-36-TC73-F8-3	CXM-6-35-90-36-TC73-F8-2
	4000K	818	760	900	CXM-6-40-90-36-TC71-F8-3	CXM-6-40-90-36-TC71-F8-2
		808	750	890	CXM-6-40-90-36-TC73-F8-3	CXM-6-40-90-36-TC73-F8-2

Notes:

1. Luminus maintains a +/- 6% tolerance on flux measurements.
2. Luminus maintains a +/- 2% tolerance on CRI measurements.



Ordering Information

Part Number Nomenclature

All Luminus COB products are packaged and labeled with part numbers as outlined in the table on page 2. Luminus may include any smaller chromaticity bin that is contained in the larger bin as part of the ordered part. When shipped, each package will contain only a single flux and chromaticity bin. The part number designation is as follows:

CXM	6	NN	XX	VV	QQPP	FG	W
Product Family	LES ¹	CCT ²	Minimum CRI ³	Typical Voltage	Package Configurator ⁴	Flux Bin	Chromaticity Bin
Chip on Board, Multi-die	6 mm LES diameter	See Note 2 below	90: CRI > 90	Volts (V) 36: 36V	TC70 TC71 TC73	Lumens	See page 4 for bins

Notes:

1. Light Emitting Surface (LES) Diameter.
2. Correlated Color Temperature (CCT), NN nomenclature corresponds to the following:

27 = 2700K	40 = 4000K
30 = 3000K	50 = 5000K
35 = 3500K	65 = 6500K
3. Minimum Color Rendering Index (CRI).
4. TC is a standard substrate with sulfur resistance process; 7 means Lux Generation 5 Pro COB products, 0 means a product with chromaticity on the BBL, 1 and 3 mean a product with chromaticity below BBL.
5. Luminus part numbers may be accompanied by prefixes or suffixes. The most common is the "Rev01" suffix indicating a part is fully released and carries a full warranty. These additional characters may appear on shipping labels, packing slips and invoices. In all cases the basic part number described above will always be included.

CCT, CRI and R9 Values

Correlated Color Temperatures	XX Value	CRI	R9 ¹
2700K, 3000K, 3500K, 4000K, 5000K, 6500K	90	>90	>50


Note:

1. R9 values have a tolerance of +/- 5%.



Binning Structure

Chromaticity Binning Diagram ¹ -TC70 On BBL



The following tables describe the chromaticity bin center points, the orientation angle for the MacAdam ellipse, and the maximum radii for the ellipses. The ANSI Bins are provided for reference.

CCT	Center point		Angle(deg)	3-step Bin		2-step Bin	
	x	y	Φ	a	b	a	b
2700K	0.4578	0.4101	53.7	0.0081	0.0042	0.0054	0.0028
3000K	0.4338	0.4030	53.2	0.0083	0.0041	0.0056	0.0027
3500K	0.4073	0.3917	54.0	0.0093	0.0041	0.0062	0.0028
4000K	0.3818	0.3797	53.7	0.0094	0.0040	0.0063	0.0027
5000K	0.3447	0.3553	59.6	0.0082	0.0035	0.0055	0.0023
6500K	0.3123	0.3282	58.6	0.0067	0.0029	0.0045	0.0019


Note:

1. Luminus maintains a +/- 0.005 tolerance on chromaticity (CIEx and CIEy) measurements.



Binning Structure

Chromaticity Binning Diagram ¹ - TC71 (Sensus® - Hospitality White)



The following tables describe the chromaticity bin center points, the orientation angle for the MacAdam ellipse, and the maximum radii for the ellipses. The ANSI Bins are provided for reference.

CCT	Center point		Angle(deg)	3-step Bin		2-step Bin	
	x	y	Φ	a	b	a	b
2700K	0.4591	0.4055	53.70	0.0081	0.0042	0.0054	0.0028
3000K	0.4348	0.3977	53.20	0.0083	0.0041	0.0056	0.0027
3500K	0.4077	0.3864	54.00	0.0093	0.0042	0.0062	0.0028
4000K	0.3812	0.3735	53.70	0.0094	0.0040	0.0063	0.0027


Note:

1. Luminus maintains a +/- 0.005 tolerance on chromaticity (CIEx and CIEy) measurements.



Binning Structure

Chromaticity Binning Diagram ¹ - TC73 (Sensus® - Brilliant White)



The following tables describe the chromaticity bin center points, the orientation angle for the MacAdam ellipse, and the maximum radii for the ellipses. The ANSI Bins are provided for reference.

CCT	Center point		Angle(deg)	3-step Bin		2-step Bin	
	x	y	Φ	a	b	a	b
3000K	0.4239	0.3836	53.20	0.0083	0.0041	0.0056	0.0027
3500K	0.3999	0.3736	54.00	0.0093	0.0041	0.0062	0.0028
4000K	0.3759	0.3616	53.70	0.0094	0.0040	0.0063	0.0027

Note:

1. Luminus maintains a +/- 0.005 tolerance on chromaticity (CIEx and CIEy) measurements.



Absolute Maximum Ratings

Parameter		Symbol	Value	Unit
Forward Current	Typical	$I_{f\text{ typ}}$	150	mA
	Maximum	$I_{f\text{ max}}$	350	
Power Dissipation	Typical	$P_{d\text{ typ}}$	4.9	W
	Maximum	$P_{d\text{ max}}$	12.0	
Operating Case Temperature	Maximum	T_c	105	°C
Junction Temperature	Maximum	T_j	120	°C



Characteristics^{1,2,3}

Parameter		Symbol	Value	Unit
Light Emitting Surface Diameter		LES	6.8	mm
Forward Voltage	Minimum	$V_{f\min}$	30.5	V
	Typical	$V_{f\text{typ}}$	32.5	
	Maximum	$V_{f\max}$	36.5	
Viewing Angle		$2\theta_{1/2}$	120	°
Thermal Resistance (junction-to-case)		$R_{\text{th J-C}}$	0.9	°C/W


Notes:

1. Device measurements are at $T_j = 85^\circ\text{C}$.
2. To prevent damage refer to operating conditions and derating curves for appropriate maximum operating conditions.
3. Voltage is rated at typical forward current. For voltage at higher drive current, refer to performance graphs.
4. Please use ray files for all optics designs.
5. Device operation not recommended at drive currents less than 10% of the typical value.
6. Caution must be taken not to stare at the light emitted from these LEDs. Under special circumstances, the high intensity could damage the eye.
7. All product operating specifications are subject to change without advance notice.




Relative Luminous Flux vs Forward Current

$T_j=85^{\circ}\text{C}$




Relative Luminous Flux vs Temperature

$I_f=150\text{ mA}$




Forward Voltage vs Forward Current

$T_j=85^{\circ}\text{C}$




Forward Voltage vs Temperature

$I_f=150\text{ mA}$




Relative Chromaticity vs Forward Current

$T_j=85^{\circ}\text{C}$



Relative Chromaticity vs Temperature

$I_f=150\text{ mA}$






Angular Distribution and Typical Spectrum


Angular Distribution

$T_j = 85^{\circ}\text{C}$



Polar Distribution


$T_j = 85^{\circ}\text{C}$






Relative Spectral Power Distribution

T_j= 85°C




Derating Curve





Mechanical Dimensions¹



Note:
1. Unless otherwise specified, tolerance is ± 0.3mm.



Shipping Tray Outline




Packing Configuration:

- 80 pcs per tray and 5 trays are stacked together to be sealed in an anti-static bag.
- The anti-static bag is boxed for easier storage, 400 pcs per box.



Shipping Label

Label on Packaging Box



Label model -- for illustration only

Notes:

- ① Manufacturer part number, flux bin and chromaticity bin
- ② Customer part number
- ③ Rev.01 indicates a fully released product
- ④ Box ID
- ⑤ Production ID
- ⑥ Total number of units in a box



Technology Overview

Luminus Chip-on-Board (COB) LED series have consistently delivered the highest lumen performance with the best color quality of any COB supplier. Driving performance enhancements through each generations of COB products has provided Luminus a comprehensive understanding of the lighting market for directional sources positioning Luminus as the COB manufacturer of choice for the most discriminating lighting manufacturers.

Reliability

Designed from the ground up, the Luminus COB LED is one of the most reliable light sources in the world today.

UL and IEC Recognized Compliance

Luminus COB arrays are tested in accordance with ANSI/UL 8750 to ensure safe operation for their intended applications. Further, Luminus maintains IEC-62031 safety ratings on all COB products.

REACH & RoHS Compliance

All LED products manufactured by Luminus are REACH and RoHS compliant and free of hazardous materials, including lead and mercury.

Test Specifications

Every Luminus LED is fully tested to ensure it meets the high quality standards customers have come to expect from Luminus' products.

Traceability

Each Luminus COB LED is marked with a 2D bar code that contains a unique serial number. With this serial number, Luminus has the ability to provide customers with actual test data measurements for a specific LED. In addition, the 2D bar code is linked to manufacturing date codes that enables traceability of production processes and materials.

Testing Temperature

Luminus COB products are measured at temperatures typical for the LED operating in the fixture. Each device is tested at 85°C junction temperature eliminating the need to scale data sheet specifications to real world situations.

Chromaticity Bin Range

Chromaticity binning delivers color consistency for every order. Standard products are delivered with a 3-step MacAdam ellipse. This ensures color performance matching in the application. For the most demanding application, Luminus is one of only a few companies that can provide a 2 SDCM bin distribution. These tightly controlled, small distribution bins provide customers predictable, repeatable colors.



Handling Notes

Luminus products are designed for robust performance in general lighting application. However, care must be taken when handling and assembling the LEDs into their fixtures. To avoid damaging Luminus COBs please follow these guidelines.

The following is an overview of the application notes detailing some of the practices to follow when working with these devices. More detailed information is available on the Luminus web site at www.luminus.com.

General Handling

Devices are made to be lifted or carried with tweezers on two adjacent corners opposite the contact pads. At no time should the devices be handled by or should anything come in contact with the light emitting surface (LES) area. This area includes the yellow colored circular area and the ring surrounding it. There are electrical connections under the LES which if damaged will cause the device to fail. In addition, the ring frame itself should not be used for moving, lifting or carrying the device. Also do not attach any optics or mechanical holders to the ring as it is not capable of handling the mechanical stress.

Storage Condition

Please follow the conditions below.

Before opening	Temperature 5~30°C, relative humidity less than 60%.
After opening	Temperature 5~30°C, relative humidity less than 60%. After opening, LED should be kept in an aluminum moisture proof bag with a moisture absorbent material.
Avoid Corrosive gas	Avoid exposing to air with corrosive gas. If exposed, contact pad solderability may be affected. More detailed information is available on the Luminus Applications Resources web pages.

Static Electricity

Luminus COBs are electronic devices which can be damaged by electrostatic discharge (ESD). Please use appropriate measures to assure the devices do not experience ESD during their handling and or storage. ESD protection guidelines should be used at all time when working with Luminus COBs.

Storage	Luminus products are delivered in ESD shielded bags and should be stored in these bags until used.
Transporting	When transporting the devices from one assembly area to another, ESD shielded carts and carriers should be used.
Assembly	Individuals handling Luminus COBs during assembly should be trained in ESD protection practices. Assemblers should maintain constant conductive contact with a path to ground by means of a wrist strap, ankle straps, mat or other ESD protection system.



Chemical Compatibility

The resin material used to form the LES can get hydrocarbons from the surrounding environment. As a result, certain chemical compounds (H₂SO₄, H₂S, SO₂, NH₃, H₃PO₄, etc.) are not recommended for use with the Luminus products. Use of these compounds can cause damage to the light output of the device and may permanently damage the device. Please refer to the table below for a list of the compounds not recommended for use with the Luminus COB products.

Common Chemicals Know to Adversely Affect Luminus Devices		
Acetates	Ethers	Potassium hydroxide
Acetic acid	Cl, F or Br containing compounds	Siloxanes
Acrylates	Liquid hydrocarbons	Sodium Hydroxide
Aldehydes	Hydrochloric Acid	Sulfur compounds
Aldehydes	Ketones	Sulfuric Acid
Amines	Nitric Acid	Toluene
Benzene	Phosphoric acid	Xylenes
Dienes		

Thermal Interface Material (TIM)

Proper thermal management is critical for successful operation of any LED system. Excess operating temperature can reduce the light output of the device. Excessive heating can cause permanent damage to the device. Proper TIM material is a crucial component for effective heat transfer away from the LED during normal operation. Please refer to www.luminus.com for specific recommendations for TIM solutions.

Please refer to https://download.luminus.com/datasheets/Luminus_APN-002319_Rev_04.pdf for more application note information.



Revision History

Rev	Date	Description of Change
01	07/14/2026	Initial release